



ENERCO

INDUSTRIAL, HIGH SPEED DOORS & LOADING BAYS

PRODUCT DATA SHEET: Delta Protect Bollards and protection barriers





Delta Protect bollards and protection barriers

Protecting critical areas of work environments, such as walls, doors and equipment

We supply, install and maintain Delta Protect security bollards and protection barriers for customers across the UK, using a modular design that allows for quick and easy replacement, together with being demountable for reuse.

Our security and protection products are resistant to harsh environmental factors, acids, detergent and UV discolouration and can operate within temperatures of +80°C to -100°C. They are also low maintenance, shockproof and cost effective due to the single rod fixing design.

The security bollards and protection barriers we supply and install are designed to avoid failure of the surrounding fixing area, should impact occur. The specialist materials used have degrees of elasticity that ensure high resistance to impact, which when combined with a unique anchoring system, also help to absorb sound.

Protect your work environment, machinery and improve safety using the Enerco crash and impact barriers, designed for warehouse, food and manufacturing facilities.

Delta Protect Key features & benefits

- Modular approach means bollards and barriers can be quickly replaced when damaged
- Protect important areas and equipment from damage
- Modern, specialist materials used in the construction of our bollards and barriers
- Resistant to harsh environmental factors
- Designed with specialist sectors such as the food industry in mind
- Functions at extreme temperatures from +80°C to -100°C
- Reusable and demountable modular system
- Highly impact resistant, with elastic materials used
- Unique Stainless Steel anchoring system to absorb impact, sound & avoid corrosion
- Designed to avoid failure of the surrounding fixing area
- Suitable for Pharma & food preparation areas
- Low maintenance, shockproof, single rod fixing design
- Resistant to acids, detergent and UV discolouration



Delta Protect Bollards



REF	DIAMETER	HEIGHT	STEELROD DIAMETER
B230	70mm	230mm	M-16*
BB400	100mm	400mm	M-30
B400	120mm	400mm	M-30
B500	120mm	500mm	M-30
B800	120mm	800mm	M-30

* Manual pallet truck only



Delta Protect Single Guardrail

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
GA20	70mm	70mm	125mm	2000mm	M-16
GA15	70mm	70mm	125mm	1500mm	M-16
GA10	70mm	70mm	125mm	1000mm	M-16
GA05	70mm	70mm	125mm	500mm	M-16

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
GB20	100mm	100mm	155mm	2000mm	M-20
GB15	100mm	100mm	155mm	1500mm	M-20
GB10	100mm	100mm	155mm	1000mm	M-20
GB05	100mm	100mm	155mm	500mm	M-20

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
GR20	120mm	120mm	175mm	2000mm	M-20
GR15	120mm	120mm	175mm	1500mm	M-20
GR10	120mm	120mm	175mm	1000mm	M-20
GR05	120mm	120mm	175mm	500mm	M-20



Delta Protect Double Guardrail

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
2GA20	70/55mm	70mm	240mm	2000mm	M-16
2GA15	70/55mm	70mm	240mm	1500mm	M-16
2GA10	70/55mm	70mm	240mm	1000mm	M-16
2GA05	70/55mm	70mm	240mm	500mm	M-16

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
2GB20	100/55mm	100mm	300mm	2000mm	M-20
2GB15	100/55mm	100mm	300mm	1500mm	M-20
2GB10	100/55mm	100mm	300mm	1000mm	M-20
2GB05	100/55mm	100mm	300mm	500mm	M-20

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
2GR20	120/55mm	120mm	340mm	2000mm	M-20
2GR15	120/55mm	120mm	340mm	1500mm	M-20
2GR10	120/55mm	120mm	340mm	1000mm	M-20
2GR05	120/55mm	120mm	340mm	500mm	M-20



Delta Protect Pedestrian Barrier

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
BAL20	120/55mm	INF. 20mm./ SUP 70mm	800mm	2000mm	M-20
BAL15	120/55mm	INF. 20mm./ SUP 70mm	800mm	1500mm	M-20
BAL10	120/55mm	INF. 20mm./ SUP 70mm	800mm	1000mm	M-20
BAL05	120/55mm	INF.120mm./ SUP 70mm	800mm	500mm	M-20

Double Pedestrian Barrier

REF	VERTICAL DIAMETER	HORIZONTAL DIAMETER	HEIGHT	LENGTH	STEELROD DIAMETER
2BAL20	120/55mm	INF. 20mm./ SUP 70mm	1000mm	2000mm	M-20
2BAL15	120/55mm	INF. 20mm./ SUP 70mm	1000mm	1500mm	M-20
2BAL10	120/55mm	INF. 20mm./ SUP 70mm	1000mm	1000mm	M-20
2BAL05	120/55mm	INF.120mm./ SUP 70mm	1000mm	500mm	M-20

Polyethylene Wall Protection

REF	LENGTH	WIDTH	THICKNESS
PE500 150/15W	2000mm	150mm	15mm
PE500 150/20W	2000mm	150mm	20mm
PE500 200/15W	2000mm	200mm	15mm
PE500 200/20W	2000mm	200mm	20mm
PE500 250/15W	2000mm	250mm	15mm
PE500 250/20W	2000mm	250mm	20mm
PE500 300/20W	2000mm	300mm	20mm
PE500 500/20W	2000mm	500mm	20mm

Delta Protect Polyethylene Socket

REF	LENGTH	WIDTH	THICKNESS
PE500 150/20S	2000mm	150mm	20mm
PE500 210/20S	2000mm	210mm	20mm
PE500 300/20S	2000mm	300mm	20mm
PE500 500/20S	2000mm	500mm	20mm
PE500 1000/20S	2000mm	1000mm	20mm