

## Delta Guard 3800 Built On Security Shutters

### Product Data Sheet 2 / 3

#### Product Description

Our Delta Guard 3800 built on security window shutters have been developed to provide an architecturally acceptable answer to the growing need for vandalism and burglary protection on domestic and commercial property. The unobtrusive design also helps in meeting the demands of many of the more stringent planning authorities.

The uniquely neat finish of security window shutters is particularly evident when they are built on to an existing building with compact aluminium boxes, styled to minimise their visual impact. The slim-line finish even makes the internal fitting of window shutters a frequent choice. Our continuous programme of product development has produced a compact shutter of exceptional strength for small to medium size apertures.

Window shutters are easy to operate from inside, manually or electrically. Where desirable punched or perforated slats can be added to provide varying levels of vision and light.

Countrywide installations include windows and doors on city centre, suburban and rural homes, offices, factories, sports centres, computer rooms and golf clubs. In short, any building where security is a concern from the outset. Unlike many other designs the Delta Guard 3800 is manufactured from solid aluminium profiles double walled to provide higher security.

Overall minimum and maximum widths are; minimum width 500mm, maximum size 4000mm wide x 5000mm high, maximum area 12sqm, curtain weight is calculated at 8kg/sqm.



#### Shutter box

Die cast Aluminium End Plates with 2 piece Roll Formed Aluminium Casing. Larger sizes will be supplied with zinc plates, steel end plates.

#### Guide Rail

Extruded Aluminium with box section for fixing/reinforcement. High-density 6mm Pile Brush Seals, H 30 (60mm Guides) are standard. Other sizes are available upon request. Can be fitted with high security guide rails.

#### Shutter Slat- CD 38

Made from double walled extruded aluminium 38mm deep, this special design coils to a small box size but gives considerable strength through the double wall construction. Suitable when security is paramount. The curtain can be mixed with vision sections of CD38 lath to give partial vision through the door when closed.



#### Finish

Standard colours for curtain slats. White RAL 9010, Brown RAL 8014 and Cream 1015.

Standard colour for bottom slats, box canopy and guides. White RAL 9010, Dark Brown BS 08 B29.

Other powder-coated colours are available on request.

### Operation

Single-phase 240v motors are required on larger shutter over 7sqm and are optional on smaller shutters. The tubular motor fits inside the axle and draws approximately 250 watts, 3 amps. Operation is by rocker switch, key switch or remote control. A manual override can be specified to operate from inside only. Multi shutter electric installations can be wired to operate from central or group switches, details available on request.

Other operators include manual spring up to 7sqm, rod crank up to 3.5sqm, geared belt up to 3sqm and swivel belt up to 2sqm.

### Security. (Manual Shutter Only)

A spring loaded lock operates automatically when the shutter is fully lowered. Security angle on the cill for shutters to sit down behind is recommended on wide or vulnerable installations. Extruded slats must be specified for security.

### Shading/Blackout

The shutters can be stopped at any point to be used for shading. This is enhanced by the optional light slits on the foam filled slats. When the shutter is fully closed it is effectively a blackout blind.

### Thermal Conductivity.

The K value of a double glazed window fitted with an aluminium shutter is further improved by 35% from 1.8 to 2.6 w/m<sup>2</sup>K.

### Maintenance

Window shutters primarily require keeping clean, particularly on city centre or coastal installations. Commercial installations should have a maintenance check every year. The guarantee period is 12 months.

### Warranty

The Delta Guard 3800 doors are supplied with a 24 month parts and labour warranty as standard providing the equipment is maintained in accordance with the manufacturer's instruction and not modified in any way whatsoever. Full details of the servicing requirements are available.

### Servicing

To help protect your investment and extend the effective working life of the equipment, full maintenance packages are available and, in most cases, we can maintain your existing doors.

We have Worksafe Contractor, CHAS and Construction Line accreditation as well as being active members of the Doors and Hardware Federation (DHF) where we have their seal of approval for the service and maintenance of doors. We ensure that our staff are trained to the highest standard and all have an NVQ qualification in line with current industry guidelines This NVQ is in addition to the CSCS Health and Safety, First Aid, Asbestos Awareness and other training including product training applicable to our industry and is continually being updated.



Other products in the Delta range from Enerco include: -

Delta Guard – Commercial Shutters  
Delta Check – Fire Roller Shutter  
Delta Slide – Insulated Overhead Doors  
Delta Part – High Speed Bi – Parting Doors  
Delta Steel – Steel Security Door Sets  
Delta Level – Dock Levellers  
Delta Seal – Dock Sealing Systems  
Delta Speed – High Speed Doors  
Delta Service – Service and Repairs  
Delta Glide – Garage Doors  
Bars  
Delta Glaze – Aluminium Glazed Window and Door Systems

Delta Roll – Steel Roller Shutter Doors  
Delta Secure – High Speed Security Doors  
Delta Insudoor – Insulated Roller Shutters  
Delta Strip – Strip Curtains  
Delta Fold – Steel Sliding Folding Shutters  
Delta Lift – Scissor Lifts  
Delta Shield – Perimeter Security  
Delta Grille – Retractable Window Grilles  
Delta Load – Loading Bay Accessories  
Delta Bar – Fixed & Removable Security Window

Please contact our sales team for more information on 01525 289322 or a brochure. Alternatively visit our web site [www.enerco.co.uk](http://www.enerco.co.uk) or [www.enercohighspeeddoors.co.uk](http://www.enercohighspeeddoors.co.uk)

We reserve the right to change the specification of the product and product data sheet without prior notification